



JP2167726

Biblio

Page 1

Drawing

esp@cenet

PREPARATION OF TRIM FOR CAR


Patent Number: JP2167726
Publication date: 1990-06-28
Inventor(s): MIHO TOSHIMI
Applicant(s): NISHIKAWA KASEI KK
Requested Patent: ☐ JP2167726
Application Number: JP19880324003 19881221
Priority Number(s):
IPC Classification: B29C65/04
EC Classification:
Equivalents:

Abstract


PURPOSE: To inexpensively obtain a trim by integrally bonding cloth to the main body of the interior product without providing an engaging jig such as a fastener by applying a high frequency magnetic field between both high frequency electromagnetic heating electrodes while holding a mesh like article between said electrodes under pressure.

CONSTITUTION: A ring-shaped metal net D as a metal mesh like article is set to the outer periphery of an armrest part b1 being a cloth bonding part. A trim main body B to which the metal net D and cloth C are set is placed on the lower high frequency electromagnetic heating electrode 1 of a high frequency electromagnetic heating apparatus equipped with lower end upper high frequency electromagnetic heating electrodes 1, 2 integrated up and down in such a state that the horizontal posture thereof is held to be set between both electrodes 1, 2. A high frequency magnetic field is applied between the high frequency electromagnetic heating electrodes 1, 2 to heat the metal net D. By this method, the resin of the outer periphery of the armrest part b1 of the trim main body D made of a polyolefinic resin is melted by the heat of the metal net D. The molten resin is infiltrated in the outer periphery of the cloth C to obtain a door trim A wherein the cloth C is integrally bonded to the trim main body B.


Data supplied from the esp@cenet database - 12




第 1 図




第 2 図



第 5 図



第 4 図



第 3 図